



# Safe T Bar Inc. - L Bar Specialty Grab Bar

**USA Manufactured and Packaged in Minnesota. STB grab bar products - Exceed ADA, ANSI and Federal Codes.**



Material used in manufacturing the grab bar products is 304 stainless steel 18-8 chromium nickel. Tubing 18 gauge 1 1/2" OD, wall clearance is 1 1/2", include 304 stainless steel screws and individually boxed. Standard flange washer mountings are Exposed Mount, however Snap Mount Conceal and Anti Bacteria Safe T Ring Conceal are also available. All flange washer are 3" OD (outside diameter). See Mounting options for additional detail/specifications.

**Tubing extends through the flange washer and is full fusion Tig (heliarc fused [Stronger] - not wire feed or filler) and welded to Military standards to form a single unit. The recessed (bossed); flanged washer keeps the weld away from installation to allow the grab bar to lay flat against the mounting surface. Flange Washer Mounting holes are true to ± 1/8".**


### Safe T Bar GRIP TIGHT™ NON- SLIP surface - ASSURANCE OF POSITIVE GRIPPING – It Grips you!

Safe T Bar Inc. features the exclusive "GRIP-TIGHT™" surface and is our standard finish. Grip Tight™ is permanently etched in the stainless steel bar, it's not an added material, effective against slipping when the user's hands are wet and soapy. Grip Tights™ color originates from the mechanical process to the 304 stainless steel, the surface is easy to clean, will not peel or create bacteria.



**Custom sizes and finishes;** Custom Bar is any alterations to our standard sizes, finishes and types of grab bars.

Inquire by Contacting Safe T Bar Inc. 1 - 800 -444 - 8855


**L Bar style Grab Bar** offers a continuous grab bar which is vertical and horizontal. With two 90° bent knuckles back to the wall and a third 90° bend to offer a continuous grab bar. L Bar is installed on one wall and needs to be specified as Left or Right side. Each L Bar has a support leg; 2020 is located on knuckle, other Lbars 4 1/2" on center of tube located on short leg. Standard lengths; 20" x 20", 16" x 32", 18" x 32", Grip Tight™ finish, include stainless steel screws and individually boxed.



2020 L Bar Universal



16 / 1832 L Bar **Left Side**



16 / 1832 L Bar **Right Side**

Item # 20" x 20"	
STB2020GT	Exp Mount
STB2020GTC	ABSTR Conceal
STB2020GTSM	Snap Mount Conceal

Item # 16" x 32"	
STB1632GTR	Exp Mount
STB1632GTRC	ABSTR Conceal
STB1632GTRSM	Snap Mount Conceal
STB1632GTL	Exp Mount
STB1632GTLC	ABSTR Conceal
STB1632GTLSM	Snap Mount Conceal

Exp Mount  
 ABSTR Conceal  
 Snap Mount Conceal  
 Exp Mount  
 ABSTR Conceal  
 Snap Mount Conceal

Item # 18" x 32"	
STB1832GTR	Exp Mount
STB1832GTRC	ABSTR Conceal
STB1832GTRSM	Snap Mount Conceal
STB1832GTL	Exp Mount
STB1832GTLC	ABSTR Conceal
STB1832GTLSM	Snap Mount Conceal

Safe T Bar Grab Bar products are rigorously inspected to ensure safety and quality of our products. Each Grab Bar product is individually handled and inspected a minimum of 14 point step inspections.

**Thank you for the opportunity of providing you with Safe T Bar Inc. products, improving independence and safety.**